

TSQ



Forest trench with low PTO, rotor with fixed tools of type Q, to cut branches, bushes and small trees up to a diameter of 20 cm.

Tractor power required: from 50 to 90 HP, designed to demand low power and high rotor efficiency.

Features Standard

- Transmission: Unique
- Type of coupling: Three-point coupling, cat. II., PDF 540 rpm,
- Rotor rotation frequencies at 540 min-1: 2300
- Hydraulic motor displacement: 22cc-27cc with gears
- External rotor diameter (mm): 430
- Type of hammer and weight: Fixed square, reversible 180° toncsten, type Q 1Kg
- Number of belts: 4
- Number of counter knives: 1

MODEL					
	m	m	Kg	HP	Nº
TSQ 160	1,6	1,82	850	60-80	33
TSQ 180	1,8	2,02	960	70-90	39
TSQ 200	2,0	2,22	1080	90-110	45
TSQ 230	2,3	2,52	1210	110-130	51



STANDARDS DOTATION				
MODEL	TSQ 160	TSQ 180	TSQ 200	TSQ 230
WORKING WIDTH (cm)	160	180	200	230
TOTAL WIDTH (cm)	182	202	222	252
TRANSMISSION	Unique	Unique	Unique	Unique
TYPE OF COUPLING	Three-point hitch, cat. II., PDF 540 rpm,	Three-point hitch, cat. II., PDF 540 rpm,	Three-point hitch, cat. II., PDF 540 rpm,	Three-point hitch, cat. II., PDF 540 rpm,
NUMBER OF HAMMERS (SERIE)	33	39	45	51
ROTOR ROTATION FREQUENCIES AT 540 MIN-1	2300	2300	2300	2300
EXTERNAL ROTOR DIAMETER (mm)	430	430	430	430
TYPES OF HAMMER AND WEIGHT	Fixed squares, reversible 180° toncsten, type Q 1Kg	Fixed squares, reversible 180° toncsten, type Q 1Kg	Fixed squares, reversible 180° toncsten, type Q 1Kg	Fixed squares, reversible 180° toncsten, type Q 1Kg
NUMBER/TYPES OF BELTS	4	4	4	4
NUMBER OF COUNTER KNIVES	1	1	1	1
WEIGHT (Kg) WITHOUT ACCESSORIES	850	960	1080	1210
TRACTOR POWER (HP)	60-80	70-90	90-110	110-130
ANTI-WEAR PADS	YES	YES	YES	YES
REAR COVER	YES - HYDRAULICS	YES - HYDRAULICS	YES - HYDRAULICS	YES - HYDRAULICS

