

TLPF UX



Tranchée forestière avec prise de force basse, rotor avec outils fixes de type Q, pour couper des branches, des buissons et des petits arbres jusqu'à un diamètre de 25 cm.

Puissance du tracteur requise : de 100 à 150 HP.

Features Standard

- Transmission: Unique
- Type of coupling: Three-point coupling, cat. II., PDF 1000 rpm,
- Rotor rotation frequencies at 1000 min-1: 1000
- External rotor diameter (mm): 510
- Number of belts: 5
- Number of counter knives: 1 in the chassis, 1 in the rear door

MODEL					
	m	m	Kg	HP	N°
TLPF UX 160	1,6	1,8	1180	100-120	33
TLPF UX 180	1,8	2,0	1320	100-120	39
TLPF UX 200	2,0	2,2	1490	120-150	45
TLPF UX 220	2,2	2,4	1630	130-150	51



STANDARDS DOTATION				
MODEL	TLPF-UX 160	TLPF-UX 180	TLPF-UX 200	TLPF-UX 220
WORKING WIDTH (cm)	160	180	200	220
TOTAL WIDTH (cm)	180	200	220	240
TRANSMISSION	Unique	Unique	Unique	Unique
TYPE OF COUPLING	Three-Point Hitch, Cat. II., PDF 1000 rpm,	Three-Point Hitch, Cat. II., PDF 1000 rpm,	Three-Point Hitch, Cat. II., PDF 1000 rpm,	Three-Point Hitch, Cat. II., PDF 1000 rpm,
ROTOR ROTATION FREQUENCIES AT 1000 MIN-1	1000	1000	1000	1000
ROTOR LINEAR SPEED PDF 1000 MIN-1 (m/s)	2300	2300	2300	2300
EXTERNAL ROTOR DIAMETER (mm)	510	510	510	510
WEIGHT OF HAMMERS	1,7 Kg	1,7 Kg	1,7 Kg	1,7 Kg
NUMBER/TYPES OF BELTS	5	5	5	5
NUMBER OF COUNTER KNIVES	"1 IN CHASSIS 1 IN REAR DOOR"	"1 IN CHASSIS 1 IN REAR DOOR"	"1 IN CHASSIS 1 IN REAR DOOR"	"1 IN CHASSIS 1 IN REAR DOOR"
WEIGHT (Kg) WITHOUT ACCESSORIES	1180	1320	1490	1630
TRACTOR POWER (HP)	100-120	100-120	120-150	130-150
ANTI-WEAR PADS	YES	YES	YES	YES
REAR COVER	YES-HYDRAULICS	YES-HYDRAULICS	YES-HYDRAULICS	YES-HYDRAULICS
HEIGHT CONTROL	YES, ADJUSTABLE	YES, ADJUSTABLE	YES, ADJUSTABLE	YES, ADJUSTABLE

