

TWIN AUTOLEVEL ELX 280



STANDARD ALLOCATIONS	
MOTOR	ISUZU 3CC1 23 KW - 30 HP
TIRES	27X10-15,3 TVS IM45 PR8 TL 6/161-205 MEFRO.
DIRECTION	4 wheels with 4 different directions, selectable on the screen
TRACTION	4-wheel drive (4 independent engines with double displacement)
BRAKES	Hydraulic parking brake. Negative on anterior
TRANSMISSION	Hydrostatic advance with proportional lever
CONTROL	Works with solenoid valves and electrical manipulators both from the console to facilitate controls.
SPEED	Minimum 100m/h — Maximum 8,5Km/h
TOTAL WEIGHT	3500 Kg
ROLLS	Possibility of running track on moving platform
AVAILABLE SIZES	L1 = 1400 / 1500 / 1600 / 1700 / 1800 L2 = 1400 / 1500 / 1600 / 1700 / 1800

OPTIONS	
MOTOR	ISUZU 3CE1 25 KW - 35 HP / Yanmar 3TNV88 25 KW – 35 HP
BRAKES	Rear axle drum brake
TIRES	31x15.50-15 PR8
TRACTION	4 Drives Wheels
COMPRESSOR	Abac 450 LT / Abac 650 LT **** 50 LT air reserve
FORKLIFTS	Available in scissors or vertical with possibility of double forks
ROLLS	Motorized Raceway

