


OPTIONS		
MOTOR	ISUZU 3CE1 25 KW - 35 HP / Yanmar 3TNV88 25 KW - 35 HP	
TRANSMISSION	With proportional joystick	
TIRES	31x15.50-15 PR8	
TRACTION	4 Drives Wheels	
COMPRESSOR	Abac 450 LT / Abac 650 LT **** 50 LT air reserve	
CLUTCH	"Slow/Fast with double travel. Total 4 speeds Minimum 100 m/h *** Maximum 20 KM/h"	
FORKLIFTS	Available in scissors or vertical with possibility of double forks	
ROLLS	Motorized roller track	

STANDARD ALLOCATIONS	
MOTOR	ISUZU 3CC1 22 KW - 30 HP
TIRES	11,5/80-15,3 PR12 IM45 TL TVS 9,00 5-94/140 MEFRO.
DIRECTION	Power steering 80 cm 3 (front axle direction)
TRACTION	4-wheel drive
BRAKES	Hydraulic parking brake.
TRANSMISSION	Hydrostatic advance with proportional lever
CLUTCH	2 Speeds with manual control
CONTROL	Works with solenoid valves and electrical manipulators both from the console to facilitate controls.
SPEED	Minimum 100m/h — Maximum 11,5Km/h
TOTAL WEIGHT	5000 Kg
AVAILABLE SIZES	L1 = 1800 *** 1700 / 1800 / 1900 / 2000 L2 = 1800 *** 1700 / 1800 / 1900 / 2000



ECO TECNICAS SD