

TSLQ



Forest trench with low PTO, rotor with fixed tools of type Q, to cut branches, bushes and small trees up to a diameter of 15 cm.

Tractor power required: from 50 to 90 HP, designed to demand low power and high rotor efficiency. **For tractor with low PTO (40cm).**

Features Standard

- Transmission: Unique
- Type of coupling: Three-point coupling, cat. II., PDF 540 rpm,
- Rotor rotation frequencies at 540 min-1: 2300
- Hydraulic motor displacement: 22cc-27cc with gears
- External rotor diameter (mm): 430
- Type of hammer and weight: Fixed square, reversible 180° toncsten, type Q 1Kg
- Number of belts: 4
- Number of counter knives: 1

MODEL					
	m	m	Kg	HP	Nº
TSLQ 140	1,4	1,67	625	50-90	27
TSLQ 160	1,6	1,87	670	50-90	33





STANDARDS DOTATION		
MODEL	TSLQ 140	TSLQ 160
WORKING WIDTH (cm)	140	140
TOTAL WIDTH (cm)	167	167
TRANSMISSION	Unique	Unique
TYPE OF COUPLING	Three-point coupling, cat. II., PDF 540 rpm,	Three-point coupling, cat. II., PDF 540 rpm,
NUMBER OF HAMMERS (SERIE)	27	33
ROTOR ROTATION FREQUENCIES AT 540 MIN-1	2300	2300
EXTERNAL ROTOR DIAMETER (mm)	430	430
TYPES OF HAMMER AND WEIGHT	Fixed square, reversible 180° toncsten, type Q 1Kg	Fixed square, reversible 180° toncsten, type Q 1Kg
NUMBER/TYPES OF BELTS	4	4
NUMBER OF COUNTER KNIVES	1	1
WEIGHT (Kg) WITHOUT ACCESSORIES	625	670
TRACTOR POWER (HP)	50-90	50-90
ANTI-WEAR PADS	YES	YES
REAR COVER	YES - HYDRAULIC	YES - HYDRAULIC

