

COMPACT X300



STANDARD ALLOCATIONS	
MOTOR	ISUZU 3CC1 22 KW - 30 HP
TIRES	10.0/75-15.3 PR10 TS09 TL TVS 9.00 5/94-140 MEFRO
DIRECTION	Power steering 80 cm 3 (front axle direction)
TRACTION	4 drive wheels
BRAKES	Hydraulic parking brake.
TRANSMISSION	Hydrostatic advance with proportional lever
CLUTCH	2 Speeds with manual control
CONTROL	Works with solenoid valves and electrical manipulators both from the console to facilitate controls.
SPEED	Minimum 100m/h — Maximum 7,5Km/h
TOTAL WEIGHT	4000 Kg
AVAILABLE SIZES	L1 = 1600 *** 1700 / 1800 / 1900 / 2000 L2 = 1600 *** 1700 / 1800 / 1900 / 2000

OPTIONS	
MOTOR	ISUZU 3CE1 25 KW - 35 HP / Yanmar 3TNV88 25 KW – 35 HP
TIRES	31x15.50-15 PR8
TRACTION	With Joystick
SPEED	Slow/ Fast with double displacement. Total 4 speeds Minimum 100 m/h *** Maximum 20 km/h
BRAKES	Rear axle drum brake
COMPRESSOR	Abac 450 LT / Abac 650 LT **** 50 LT air reserve
FORKLIFTS	Available in scissors or vertical with possibility of double forks
ROLLS	Motorized

